Connecting to a Non-Domain / Workgroup Windows 2012 Server with RSAT for Windows 8



We will be connecting to a non-domain joined <u>Windows 2012 Server</u> with the <u>Remote Server</u> <u>Administration Tool</u>(RSAT). In order to do this requires a Powershell command to be run on the Windows 8 client machine before attempting to connect to the workgroup server. You will need to launch the Windows Powershell prompt as Administrator. In order to do so, hit the Windows key on the keyboard to return to the Start screen. Type in "powershell" then right click the "Windows Powershell" tile and choose "Run as Administrator":

	Apps Results for "powers"
	 Windows PowerShell ISE Active Directory Module for Windows PowerShell (x86) Windows PowerShell ISE
Pin to Start	Pin to taskbar Pin to taskbar Pin to taskbar

Before you continue, the server has to appear in DNS or resides in the Hosts file on the local Win8 machine, as IP addresses are not allowed by default. So successfully ping the server by name first, then proceed. Now we need to run the command as follows:

Set-Item WSMan:\localhost\Client\TrustedHosts -Value <YourtargetServernameHere>-Force

Replace the <YourtargetServernameHere> with the server name both the short name and the fully qualified name(hint this might come from your home dsl router, mine did) of the target server. These will be added with quotations as seen here:



Now launch the RSAT tool, click on "Manage" then "Add Servers". Click on the DNS tab, type in the server by name, hit "Enter", and click on arrow to move the server to the right hand pane. Now click "OK"."

L.	Server Manager – 🗆 🔀						
Server Ma	anager 🔸 All Ser	vers - 🕄 🚩 Manage Tools	View Help				
Dashboard All Servers	SERVERS All servers 0 total	▷ (ii) ▼ (ii) ▼ ▲ Add Servers -	TASKS V				
	EVENTS All events [0 total Filter Server Name II	Active Directory DNS Import Selected	Cancel				

You will then notice that the action has an alarm. Right click the server and select "Manage As", fill in the credentials as servername\administrator(or whichever local admin account is present on the target), check the box to remember the credentials if you wish, and then click "OK."

		Server Manager – 🗆			
anager • All Servers			- (🔊 🚺 Manage	Tools View
SERVERS All servers 1 total					TASKS
Refresh failed					More>
Filter	Q				۲
Server Name IPv4 Address	Manag	eability	Last Update	Windows Activation	
win-shmute4k45 -	Kerber	os target resolution error	12/5/2012 11:19:20	AM -	
		Entre Lines Accounts	Windows Security	×	
EVENTS All events [0 total		Enter Oser Account and Password Enter the name and password of an account with user rights on the selected servers. For example, user, user@example.contoso.com, or domain\user name. Entering a blank user name and password deletes cached credentials.			TASKS
Filter Server Name ID Severit	р y Sourc	M win-shrm	ute4k45\administrator		۲
		Remember my cr	edentials	OK Cancel	

Now you should be good to go for adding Roles and Features or monitoring the server.